

1		2		3		4		5		6		7		8			
CHARACTERISTICS																	
Contact resistance										15mΩ max. (initial)			Rating			15A 125VAC or 250VAC	
Insulation resistance										100MΩ min. (at 500 VDC)			Terminal			SCREW	
Dielectric strength										1,000 VAC,50/60Hz for 1 minute between			Item No.			Z15G1305	
Mechanically service life										1,000,000 operations min.			OF max.			250~350gf	
													RF min.			114gf	
Electrically service life										100,000 operations min.			PT max.			0.4mm	
													OT min.			1.6mm	
													MD max.			0.05mm	
													OP			28.2±0.5mm	

--	--	--	--

--	--

3-M4X5.0 Terminal Screw with toothed lock washer	
--	--

0.000*±0.25°		0.000±0.005		DRAWN		DATE	
0.00°±0.5°		0.00±0.10		Ar-thur		2003/03/18	
0.0°±1°		0.0±0.20		CHECKED		DATE	
0°±2°		0±0.50		APPROVER		DATE	
ANGULAR		LINEAR		SCALE		2.5: 1	
TOLERANCE							

TITLE:		S0216D1305 CHARACTERISTICS	
FINISH			
MATERIAL:			
DWG NO.		A3	

B		C		D		E		F	
---	--	---	--	---	--	---	--	---	--