



A向

CIRCUIT DIAGRAM




SPECIFICATION

- RATING:UL C-UL:10A 125VAC
ENEC SEMKO:
6(2)A 250VAC T125/55 1E4
- CIRCUIT:ON-OFF W/Lamp SPST 3P
- VOLTAGE: 220VAC
- CONTACT RESISTANCE:30m OHMS Max
- INSULATION RESISTANCE:DC500V 100M OHMS Min
- WITHSTAND VOLTAGE:AC 1500V 1 Minute
- ELECTRICAL LIFE:10000 Cycles at Full Load
- OPERATION FORCE:300~600gf
- OPERATION TEMPERATURE RANGE:-25~+125° C

PANEL HOLE SIZE

Panel thickness	X
0.75-1.25	20.2
1.25-2.0	20.4
2.0-3.0	20.6



MATERIALS

- HOUSING:Nylon #66 UL 94V-2
- ROCKER:PC UL 94HB
- TERMINAL:Copper Alloy Ag plated
- CONTACTOR:AgSnO₂In₂O₃ (10) /Cu

喜威達企業股份有限公司
SWEETA PRODUCTS CORPORATION

设计	签名	年月日	标准化	签名	年月日
绘图	符辉	16.11.10			
审核	张雪飞				
工艺			批准		

SRL3-511/N-G-2-RE/BK-P5

TITLE	ROCKER SWITCH	SERIES	RL3-5
FUNCTION	ON-OFF W/lamp	DRAWING NUMBER	
VIEWS TYPE			