

## SWDTS(G)L、 F-6 SPECIFICATION

文件編號： E-B-AT16  
版次： C  
頁次： 1 / 4

### 1. Style

This specification describes "TACTILE SWITCH", mainly used as signal switch of electric devices, with the general requirements of mechanical and electrical characteristic.



1.1 Operating Temperature Range: -25 +70

1.2 Storage Temperature Range : -30 +80

2. Current Range: 50mA, 12 VDC


3. Type of Actuation: Tactile feedback

4. Test Sequence:

	ITEM	DESCRIPTION	TEST CONDITIONS	REQUIREMENTS
APPEARANCE	1	Visual Examination	By visual examination check without any out pressure & testing.	There shall be no defects that affect the serviceability of the product.
ELECTRIC PERFORMANCE	2	Contact Resistance	Applying a static load 1.5~2 times the operating force to the center made with a 1 kHz small current contact resistance meter.	100mΩ Max.
	3	Insulation Resistance	Measurements shall be made following application of 500 V DC potential across terminals and cover for 1 minute ±5 seconds.	100MΩ min.
	4	Dielectric Withstanding Voltage	250 V AC(50Hz or 60Hz) shall be applied across terminals and cover for 1 minute	There shall be no breakdown or flashover.
	5	Capacitance	1 MHz ±10kHz	5 pF max.
	6.	Bounce	3 to 4 operations at a rate of 1 cycles per second  	5 m seconds max.  

SWDTS(G)L、 F-6 SPECIFICATION

文件編號： E-B-AT16  
版次： C  
頁次： 2 / 4

MECHANICAL PERFORMANCE	7.	Operating Force	Applied in the direction of operation. 	OF	100±50g [.98N ±.49N]	160±50g [1.568N ±.49N]	260±50g [2.548N ±.49N]	320±80g [3.136N ±.784N]	520±130g [5.096N ±1.274N]	200 <sup>+60</sup> / <sub>-50</sub> g (62N) [1.96N <sup>+588N</sup> / <sub>-49N</sub> ] (SILICONE)	
	8.	Stroke	Placing the switch such that the direction of switch operation is vertical and then gradually increasing the load applied to the stem, the stroke distance for the stem to come to a stop shall be measured.	0.25 +0.2/-0.1 mm							
	9.	Stop Strength	Placing the switch such that the direction of switch operation is vertical, a static load of 3 kgf shall be applied in the direction of stem operation for a period of 15 seconds	As shown item 2~7							
	10.	Solder Heat Resistance	■ SMT Type 4 of 4 SWDTS(G)L、 F-6 Series	As shown in item 2~5							
	11.	Vibration	Shall be vibrated in accordance with Method 201A of MIL-STD-202F 1)Frequency: 10-55-10Hz in 1-min/cycle. 2)Direction: 3 vertical directions including the directions of operation 3)Test time: 2 hours each direction. 4)Swing distance=1.5mm	As shown in item 2~7							

**SWDTS(G)L、 F-6 SPECIFICATION**

文件編號 : E-B-AT16  
版 次 : C  
頁 次 : 3 / 4


<b>MECHANICAL PERFORMANCE</b>	12	Shock	<p>Shall be shocked in accordance with Method 213B condition A of MIL-STD-202F</p> <p>1)Acceleration; 50G 2)Action time:11±1m seconds 3)Testing Direction: 6 sides 4)Test Cycle: 3 times in each direction</p>	As shown in item 2~7	
	<b>DURABILITY</b>	13	Operating Life	<p>Measurements shall be made following the test forth below:</p> <p>1)5 mA,5 VDC resistive load 2)Applying a static load the operating force to the center of the stem in the direction of operation Static Load = OF max. 3)Rate of Operation: 1 operation 2 second 4)Cycle of Operation: 1000,000 cycle's min. For 100,160gf 500,000 cycle's min. For 200,260gf 300,000 cycle's min. For 320,520gf</p>	<p>1)As shown in item 4、 5 2)Operating force:±50% of initial force and RF follow item 7. 3)Contact Resistance: 200mΩ Max 4)Insulation Resistance: 10MΩ min 5)Bounce: 10 m seconds Max</p>
		<b>WEATHER-PROOF</b>	14	Resistance Low Temperature	<p>Following the test set forth below the sample shall be left in normal temperature and humidity conditions for an hour before the measurements are made:</p> <p>1)Temperature:-25±3 2)Time:96 hours</p>
15			Resistance High Temperature	<p>Following the test set forth below the sample shall be left in normal temperature and humidity conditions for an hour before the measurements are made:</p> <p>1)Temperature:80±2 2)Time:96 hours</p>	As shown in item 2~7
16	Resistance Humidity		<p>Following the test set forth below the sample shall be left in normal temperature and humidity conditions for an hour before the measurements are made:</p> <p>1)Temperature:40±2 2)Relative Humidity:90~95% 3)Time:96 hours</p>	<p>1)As shown in item 4~7 2)Contact Resistance: 200mΩ Max 3)Insulation Resistance: 10MΩ min</p>	

**SWDTS(G)L、 F-6 SPECIFICATION**

文件編號： E-B-AT16  
版次： C  
頁次： 4 / 4

**5. SOLDERING CONDITIONS:**

Condition for Soldering –SWDTS Series



- The condition mentioned above is the temperature on the Cu foil of the PCB surface. There are cases where board's temperature greatly differs from switch's surface be used not to allow switch's surface temperature to exceed 240 .

■ Manual Soldering

Soldering Temperature	Max.350
Continuous Soldering Time	Max. 3 seconds

■ Precautions in Handling

- 1.Care should be exercised so that flux from the upper part of the printed circuit board does not adhere to the switch.
- 2.Except for washable type do not wash the switch body.